## TGR 4340 (8x4) DXD CONSTRUCTION TRUCK



BMC



**CABIN** 

TYPF

Day Cab

CAB SUSPENSION

Mechanic

**ENGINE** 

BRAND / MODEL

Cummins L9E6E (Euro 6)

Turbo Intercooler Diesel

NUMBER OF CYLINDERS

DISPLACEMENT

8.9 L

MAXIMUM POWER

400 PS (298 kW) @ 2100 rpm

MAXIMUM TORQUE

1700 Nm @ 1400 rpm

DIAMETER & STROKE

114 mm / 145 mm

**TANKS** 

FUEL TANK CAPACITY

3001

ADBLUE TANK CAPACITY

74 L

**GEAR BOX** 

BRAND / MODEL

ZF 12 TX 1815 TO (Automatic)

ZF 12 TX 1815 TO (Automatic + Intarder)

NUMBER OF GEAR

12 Forward, 2 Reverse

**GEAR RATION** 

12,92:1; 0,77:1 (Reverse: 13;1:1 / 10,12:1)

CLUTCH

430 mm // (17") Single Disc

**AXLES** 

FRONT AXLE

LOAD CAPACITY

9000 kg +9000 kg

REAR AXLE

**Gear Ration** 

5 411

LOAD CAPACITY

16000kg + 16000 kg

SUSPENSION

FRONT AXLE

100 mm Parabolic Leaf Springs,

Telescopic Shock Absorbers

REAR AXLE

100mm Reverse Parabolic Tandem Springs

ANTI-ROLL BAR

Rear (4th) and Front (1st) Axles

**TYRES** 

SIZE / NUMBER

318/80/R22,512+1 (S) 13R/22,5 12+1 ເບາ

**RIMS** 

SI7F

9 X 22.5

**PERFORMANCE** 

TOP SPEED (LIMITED) (km/h)

TURNING RADIUS (m)

**ELECTRICAL SYSTEM** 

VOLTAGE

24 V

**BATTERIES** 

2 x 12 V / 180 Ah ALTERNATOR

120 A

(S)

(0)

STARTER MOTOR

24 V

STEERING SYSTEM

TYPE

Hydraulic

**BRAKE SYSTEM** 

BRAKE SYSTEM TYPE

Air Operated Dual Circuit Type

Ø410x200 Z-Cam Drum Brakes, ABS, ASR

RETARDER TYPE

Intarder (600 kW) (0)

**ENGINE BRAKE** 

252 kW (S)

**CHASSIS** 

CHASSIS PROFILE

Steel, 8mm+5mm (Reinforced)

STANDARD ACCESSORIES

Manually Operated Digital Air Conditioner (6 kW)

Radio/MP3/Bluetooth

2 USB +Cigarette Lighter (Driver Side)

2 USB + 12V (Passenger Side), 1 USB (Multimedia)

4 Points Independent Mechanic Cab Suspension

Cruise Control

Electrically Operated and Heated Side Mirrors

Adjustable Steering Column

Manually Operated Sunroof

Antilock Braking System (ABS)

Anti Slip Regulation (ASR)

Immobilizer

Single Key with Remote Control and Central Locking

Differential Lock

Digital Tachograph

Electrically Operated Windows

Air Suspended Driver Seat

Adjustable Driver Seat Armrest

Seat Headrest

Seatbelt Sensor (Driver)

Driver and Passanger Sun Visor

Spare Wheel

Front Fog Lamps

Electrically Operated Headlight Leveling

Front Dust Protection

Transmission PTO

Lamp Under Hood

Lamp Under Cab

Tyre Inflation Valve

HeadLight Protection Bars

Body Structure Module

**OPTIONAL ACCESSORIES** 

7" Multimedia Display

Driver Seat with Air Operated Back Support

**Heated Driver Seat** 

Adjustable Passenger Seat Armrest


Fleet Management System Socket and Module

Intarder (600 kW)

Engine PTO - REPTO

Electric Cab Lift Tire Pressure Monitoring System

Single Type Clutch System



\*For kerb weight calculation, minimum equipment, no driver, 20 liters of fuel, 5 liters of urea included. Kerb weight may change depends on optional equipments :322 Z:274 (Loaded)

[S]: Standard

**DIMENSIONS (mm)** 

F: Useful Chassis Length

A: Wheelbase

B: Overall Length

D: Overall Height

5050 9005

C: Overall Width (Excluding Mirrors) 2550

805

315/80/R 22,5: 3505 13R/22,5: 3527 6395

I: Inner Height 1670 (Tunnel Height: 190) 0: Front Overhana 1500

H: Front Track J: Rear Track S: First Step Height

K': Chassis Height

1847 315/80/R22,5: 547 13/R22,5: 570

2120

R: Inner Width

2155 315/80/R22,5: 1168

13/R22,5: 1123 P: 1. and 2. Axle Distance 1804 P1: 2. and 3. Axle Distance 3246 P2: 3. and 4. Axle Distance 1350

**KERB WEIGHTS (kg)** 

3645

WEIGHTS (kg)

G': Rear Overhang

MAXIMUM WEIGHT LOADED FRONT AXLE MAXIMUM WEIGHT LOADED REAR AXLE **GROSS VEHICLE WEIGHT** 

**TECHNICAL LEGAL** 8000+8000 8000+8000 13400+13400 9500+9500 42800 32000

2. AXLE 3210 3. AXLE 2160 4.AXI F 1970 TOTAL 10985\*

1. AXLE

BMC reserves the right to change the technical specifications of the products without prior notice (April 2024)